

# System Chart for MDX Mirrorless Housings(for Sony)

MDX-α6300/MDX-α7 II/MDX-α6000

(As of Sep,2019)

	LENS	Housings	GEAR	SUB-PORT & PORT	Anti-reflective Ring
MACRO	SEL30M35	[α6300] [α6000] [α7II]	Focus Gear(Product No.31173) <a href="#">Instructions</a>	ML Flat Port33 ★	
	SEL50M28	[α6300] [α6000] [α7II]	Focus Gear(Product No.31194)	ML Extension Ring 25+ ML Extension Ring 25+ ML Flat Port33 ★	
				ML Extension Ring 25+ ML Flat Port63	
	SEL90M28G	[α6300] [α6000] [α7II]	Focus Gear(Product No.31178) <a href="#">Instructions</a>	ML-NX Conversion Ring 30+ Extension Ring 46 with Focus Knob+ DX Macro Port 52★	
			Use auto focus *1	ML-NX Conversion Ring 30+ NX Compact Macro Port Base+ DX Macro Port 52★	
Touit 2.8/50M	[α6300] [α6000] [α7II]	Use auto focus *1	ML Extension Ring 25+ ML Extension Ring 25+ ML Flat Port33 ★		
WIDE	SEL28F20	[α6300] [α6000] [α7II]	Use auto focus *1	ML Flat Port63	
	SEL28F20 + SEL075UWC ※1	[α6300] [α6000] [α7II]	Use auto focus *1	ML-NX Conversion Ring 30+ Fisheye Dome Port 240	
				ML-NX Conversion Ring 30+ Extension Ring 40L+ NX Compact Dome Port	
SEL28F20 + SEL057FEC	[α6300] [α6000] [α7II]	Use auto focus *1	ML-NX Conversion Ring 30+ Fisheye Dome Port 240		
			ML-NX Conversion Ring 30+ Extension Ring 30L+ NX Compact Dome Port		
ZOOM	SELP1650	[α6300] [α6000] [α7II]	Zoom gear(Product No.31171)*1 *2 <a href="#">Instructions</a>	ML Flat Port33 ★	Shading Ring M40.5 *3
	SEL1018	[α6300] [α6000] [α7II]	Zoom gear(Product No.31172)*1 <a href="#">Instructions</a>	ML-NX Conversion Ring 30+ NX Compact Dome Port	Shading Ring M62 *3
	SEL1635Z	[α6300] [α6000] [α7II]	FC Zoom gear(Product No.31177)*1 <a href="#">Instructions</a>	ML-NX Conversion Ring 30+ Extension Ring 46 with Focus Knob+ Fisheye Dome Port 240	Shading Ring M72 *3
				ML-NX Conversion Ring 30+ Extension Ring 46 with Focus Knob+ NX Compact Dome Port	
SEL2870	[α6300] [α6000] [α7II]	Zoom gear(Product No.31185)*1 <a href="#">Instructions</a>	ML Extension Ring 25+ ML Flat Port63		

★:A close-up lens with M67 mount can be attached to the end of the port.

※1:Setting of the aperture value more than F8 is recommended.

\*1:Manual focus cannot be used.

\*2:The power zoom can be used with the accessory spacer.

\*3:The combination will prevent internal light reflections from the built-in flash.

\*4:Light Shielding Sponge, which prevents internal light reflections from the built-in flash.